

PC 667

Shurtape®
TRUE TO YOUR WORK™

SPECIALTY GRADE, OUTDOOR STUCCO DUCT TAPE

TYPICAL APPLICATIONS

- For protective masking of non-painted surfaces, including steel, vinyl, aluminum and anodized metals
- Use in plastering, stucco, concrete, pool and tile applications

PRODUCT FEATURES

- 14-day UV-resistant
- Easy to tear
- Removes cleanly
- Made using Polybonded CO-EX Technology®

CONSTRUCTION

Overall Grade/Function: Specialty/Extended outdoor

Backing: Waterproof, UV-resistant polyethylene film with a cloth carrier

Adhesive: Blended rubber

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)


55 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

STANDARD

METRIC

Tensile Strength	26 lbs/in width	45.5 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10 mm
Thickness	9 mils	0.23 mm
Elongation	23%	23%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

