

FP 227



PRINTABLE, HIGH ADHESION COLORED FLATBACK PAPER TAPE

TYPICAL APPLICATIONS

- For full-web flexographic printing equipment or hand-labeling applications

PRODUCT FEATURES

- High adhesion
- Flexible
- Abrasion- and oil-resistant
- Available in a variety of colors, including high-visibility fluorescents

CONSTRUCTION

Overall Grade/Function: Printable
Backing: Colored flatback paper
Adhesive: Rubber-based

STANDARD WIDTH(S)

24 mm 48 mm (for most colors)

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type II; ASTM D-4236 (all except fluorescents)

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES STANDARD METRIC

Tensile Strength	30 lbs/in width	52.5 N/10 mm
Adhesion to Stainless Steel	57 oz/in width	6.24 N/10 mm
Thickness	5.8 mils	0.15 mm
Elongation	2.5%	2.5%
Service Temperature Range	40 F to 150 F	4 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

