







33.25 [845]

30.25 [762]

33.25 [845]

30.25 [762]

PART NUN	MBER R	OLLER
DISK Ø—	COLOR— &	SETUF
1195 - XX XX -	XX -[X[X]	XX
DRUM WIDTH J MOTOR, CRANI	PLUMBI & SWIVE	ΞL
BRAKE OPTION		S

	***ALL DIMS ROUNDED TO QUARTER INCH [.5MM]			ŀ
		DIMENSION	ADD TO	l
MOTOR DRIVE SYSTEM	"M" in[mm]	WEIGHT lb [kg]	ŀ	

13.5 [343]

24 [610]

20 [508]

32 [813]

1195-1332

1195-2428

1195-2032

1195-3228

32 [813]

28 [711]

32 [813]

28 [711]

ELECTRIC MOTOR: 1/2H				6.59 [167] 26	26 [12]	26 [12] (HOSE DEPEND		l
	(12V & 24VD C,115V & 230V AC)		` '			INLET THREAD	Ì	
	AIR MOTOR (6 VANE, IRON)		5.42 [138]	8 [4]		OUTLET THREAD	Ī	
	HYDRAULIC			3.77 [96]	6 [3]	\Box	HOLE SIZES	Ī
ı	MODEL	MODEL DIA in[mm] dW in[mm]		W in[mm]	H in[mm]		CAPACITY	=
						1.5	5" (2-1/16" OD) ft[m]	
	1195-932	32 [813]	9.5 [241]	15 [381]	33.25 [845]		60 [18.2]	_
	1195-1728	28 [711]	17.5 [444]	23 [584]	30.25 [762]		85 [27]	

19 [483]

29.5 [750]

25.5 [648]

37.5 [952]

UNLISTED OPTIONS & CUSTOM REELS

SPECIFICATIONS

SPEC.

1000 PSI [69 BAR]

-40 F TO 225 F

[-40 C TO 107 C]

2" NPT FEMALE

2" NPT FEMALE

.5" [13]

CAPACITY

2" (2-9/16" OD) ft[m]

50 [15]

60 [18.2]

75 [23]

90 [29]

115 [35]

125 [38]

OPTION

1500 PSI [103 BAR]

W/ -BUXX SWIVEL

-60 F TO 400F

[-51 C TO 204 C]

1.5" NPT FEMALE

1.5" NPT FEMALE

WEIGHT lb[kg]

128 [58]

134 [61]

148 [67]

169 [77]

186 [84]

218 [99]

FEATURE

PRESSURE

TEMPERATURE

100 [30]

135 [41]

150 [46]

175 [53]

NOT ALL OPTIONS ARE LISTED, CONTACT YOUR SALES REPRESENTATIVE OR FACTORY FOR ADDITIONAL OPTIONS & CUSTOM MODIFICATIONS

S	COXR	EEL
.	5865 S Ash Avenue	Tempe, Az

1-800-COX-REEL www.coxreels.com THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND IS THE PROPERTY OF COXREELS, INC. THE COPYING, DISTRIBUTION AND UTILIZATION OF THIS DOCUMENT AS WELL AS COMMUNICATION OF ITS CONTENT TO OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF COXREELS, INC., IS PROHIBITED.

	·
TITLE:	
	1195 SERIES

MATERIAL

STEEL

INLINE NI PLATED

STEEL

NITRILE

STEEL

BRONZE, SELF LUBE

STEEL

BLUE POLYESTER

POWDER COAT

OPTIONS

302/304 STAINLESS STEEL

302 INLINE & 440 SS

90 DEGREE SS OR Ni

VITON, EPDM, AFLAS (SS OR

Ni 90 DEGREE ONLY)

RED(R), GREEN(N),

WHITE(W),

BLACK[WRINKLE(C)/

GLOSS(K)] GREY(G)

COMPONENT

PLUMBING

SWIVEL

SEALS

REEL

BEARINGS

CHAIN GUARD

FINISH

	DWG. NO.:	95 SERIES	REV.
,	11	-	
	3RD ANGLE	INTERPERT PER	SIZE: A
۷.	\odot	ASME : Y14.5M-1994 DO NOT SCALE DWG.	SHT:1 OF:2

