



MODEL	I.D.	H	L	X	M	EZ-COIL	1/4" CAPACITY	3/8" CAPACITY	1/2" CAPACITY	WEIGHT
	in[mm]	in[mm]	in[mm]	in[mm]	in[mm]		ft[m]	ft[m]	ft[m]	lb[kg]
P-LP-125	5.87 [149]	14.87 [378]	13.5 [343]	5 [127]	3 [76]	Y	25 [7.6]			27 [12]
P-LP-130	5.87 [149]	14.87 [378]	13.5 [343]	5 [127]	3 [76]		30 [9.1]			27 [12]
P-LP-135	5.87 [149]	14.87 [378]	13.5 [343]	5 [127]	3 [76]	Y	35 [11]			28 [12]
P-LP-140	6.75 [171]	18.62 [473]	17.12 [435]	6 [152]	4 [102]		40 [12]			38 [17]
P-LP-150	6.75 [171]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]	Y	50 [15]			40 [18]
P-LP-325	6.5 [165]	14.87 [378]	13.5 [343]	5.0 [127]	3.0 [76]	Y		25 [7.6]		28 [12]
P-LP-330	6.75 [171]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]	Y		30 [9.1]		37 [17]
P-LP-335	6.75 [171]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]	Y		35 [11]		38 [18]
P-LP-340	6.75 [171]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]			40 [12]		39 [17]
P-LP-350	6.75 [171]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]	Y		50 [15]		43 [19]
P-LP-415	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]				15 [4.5]	41 [18]
P-LP-425	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]				25 [7.6]	44 [20]
P-LP-430	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]	Y			30 [9.1]	45 [20]
P-LP-450	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]	Y			50 [15]	48 [22]
P-MP-320	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]			20 [6.1]		46 [20]
P-MP-325	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]			25 [7.6]		49 [23]
P-MP-330	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]			30 [9.1]		51 [23]
P-MP-335	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]			35 [11]		52 [23]
P-MP-420	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]				20 [6.1]	47 [21]
P-MP-425	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]	Y			25 [7.6]	49 [22]
P-MP-430	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]	Y			30 [9.1]	51 [23]
P-HP-120	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]			20 [6.1]		46 [20]
P-HP-125	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]	Y		25 [7.6]		48 [22]
P-HP-130	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]			30 [9.1]		50 [22]
P-HP-135	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]			35 [11]		51 [23]
P-HP-320	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]				20 [6.1]	47 [21]
P-HP-325	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]	Y			25 [7.6]	49 [23]
P-HP-330	7.0 [178]	18.62 [473]	17.12 [435]	6.0 [152]	4.0 [102]				30 [9.1]	51 [23]

SPECIFICATIONS		
FEATURE	SPEC.	OPTION
PRESSURE	SEE PG 2	-
TEMPERATURE	SEE PG 2	-
INLET THREAD	NPT FEMALE	BSP
OUTLET THREAD	NPT MALE (ON HOSE)	BSP

MATERIAL SPECIFICATIONS		
COMPONENT	MATERIAL	OPTIONS
SWIVEL	LP/MP-BRASS (1/4" - 1/2") HP- ZINC PLATED STEEL	STAINLESS STEEL (ALL)
SEALS	NITRILE	VITON, EPDM, FOOD GRADE
REEL	STEEL	STAINLESS STEEL
BEARINGS	BRONZE, SELF LUBE	-
BALL STOP	RUBBER	STAINLESS HARDWARE
LOCKING PAWL	STAINLESS STEEL	BRONZE (NON-SPARK)
FINISH	BLUE POWDER COAT (B)	RED(R), GREEN(N), WHITE(W), BLACK [WRINKLE(C)/GLOSS(K)], GREY(G) STAINLESS POLISHED (SS)

UNLISTED OPTIONS & CUSTOM REELS
 NOT ALL OPTIONS ARE LISTED. CONTACT YOUR SALES REPRESENTATIVE OR FACTORY FOR ADDITIONAL OPTIONS & CUSTOM MODIFICATIONS

COXREELS
 5865 S Ash Avenue Tempe, Az 85283
 1-800-COX-REEL www.coxreels.com
 THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND IS THE PROPERTY OF COXREELS, INC. THE COPYING, DISTRIBUTION AND UTILIZATION OF THIS DOCUMENT AS WELL AS COMMUNICATION OF ITS CONTENT TO OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF COXREELS, INC., IS PROHIBITED.

TITLE: **P SERIES**
 DWG. NO.: **P SERIES** REV. -
 3RD ANGLE INTERPERT PER ASME : Y14.5M-1994 DO NOT SCALE DWG. SIZE: A SHT:1 OF:2

